# BRILUBE technical data sheet.

# **BRILUBE 30**

#### PART OF OUR FIT RANGE OF LUBRICANTS

BRILUBE 30 has been developed as an easily applied wire rope dressing and maintenance lubricant.

It is a thixotropic wax/grease lubricant dispersed with solvent. It leaves a thin semidry film on the rope, providing excellent corrosion protection properties. Designed for maintenance treatment of wire ropes. The high penetrating ability ensures not only surface protection but also lubrication of the strands which helps to minimise wear between strands and extend the fatigue life.

### key performance differentiators

- Advanced corrosion protection
- √ Good saltwater protection
- High lubricity
- ✓ Low fling off
- ✓ Enhanced rope life
- ✓ Effective penetration
- Easy application

LUBRICANT PROPERTIES	TYPICAL VALUE
Appearance	Brown opaque fluid
Specific gravity	0.82
Film type	Grease/wax
Non-volatile content	30%
Flash point	40°C
Drying time	1 hour (20°C)

## BRIDON · BEKAERT

**Bridon-Bekaert Ropes Group** is the world's premier supplier of mission-critical advanced cords, steel wire ropes, and fibre synthetic ropes.

As a leading innovator, developer and producer of the best performing ropes and advanced cords globally, the Group provides superior value solutions to the oil & gas, mining, crane, elevator and other industrial sectors.



contact.

www.bridon-bekaert.comcontact@bridon-bekaert.com+44 (0) 1302 344010



Please refer to product safety data sheet before use.

Edition 06/2019 Version 2