



## Mobiltrans HD Series

Mobil Commercial-Vehicle-Lube , United States

Extra High Performance Transmission and Drivetrain Lubricants

### Product Description

Mobiltrans HD 10W, 30, 50, and 60 are extra high performance, heavy duty transmission and drive-train lubricants engineered to meet or exceed the requirements of the rigorous Caterpillar TO-4 specification. This product line is uniquely designed to optimise the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems

This technology combines selected base oils and an advanced additive system to deliver the precise performance parameters needed to maximise the productivity of construction, quarrying, and mining equipment operating in severe conditions. These products offer a clear performance advantage over the use of mixed fleet engine oils and previously used lubricants meeting Caterpillar TO-2.

### Features and Benefits

| Features  | Advantages and Potential Benefits   |
|---|---|
| Balanced static and dynamic friction coefficients             | Optimised clutch-friction retention and slippage control<br>Significantly improved clutch life compared to the best API CD/TO-2 engine oils |
| Compatible with modern clutch materials and elastomers        | Longer clutch life and higher performance   |
| Increased levels of anti-wear and load carrying capability    | Reduced gear wear and extended life in transmissions, gearboxes, and final drives<br>Greater productivity from reduced downtime             |
| Excellent foam control protection                             | Top performance in wet brakes; excellent control of brake chatter   |
| Excellent thermal and oxidation stability                     | Outstanding hydraulic oil stability and protection against high-pressure pump wear  |
| Lower viscosities offer very good low temperature pumpability | Reduced time from start-up to production  |

### Applications

Recommended by ExxonMobil for use in:

- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
  - Manual, powershift, and automatic transmissions where Allison C-4 fluids (SAE 10W and 30 grades) are called for including Twin Disc and transmissions calling for Type F fluids
- Most mobile equipment hydraulic applications

### Specifications and Approvals

| This product has the following approvals: | 30 | 50 | 60 | 10W |
|---|----|----|----|-----|
| ZF TE-ML 03C                              | X  |    |    | X   |

| This product has the following approvals: | 30 | 50 | 60 | 10W |
|---|----|----|----|-----|
| ZF TE-ML 07F                              | X  |    |    |     |

| This product is recommended for use in applications requiring: | 30 | 50 | 60 | 10W |
|--|----|----|----|-----|
| Allison C-4  | X  |    |    | X   |
| KOMATSU KES 07.868.1   | X  | X  |    | X   |

| This product meets or exceeds the requirements of: | 30 | 50 | 60 | 10W |
|--|----|----|----|-----|
| Caterpillar TO-4                                   | X  | X  | X  | X   |

### Properties and Specifications

| Property   | 30     | 50     | 60     | 10W     |
|--|--------|--------|--------|---------|
| Grade  | SAE 30 | SAE 50 | SAE 60 | SAE 10W |
| Density @ 15 C, kg/l, ASTM D4052                           | 0.893  | 0.906  | 0.911  | 0.888   |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 224    | 240    | 244    | 202     |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 11.2   | 18.0   | 25.2   | 6.3     |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 100    | 195    | 340    | 42      |
| Pour Point, °C, ASTM D97                                   | -18    | -15    | -12    | -33     |
| Viscosity Index, ASTM D2270                                | 97     | 100    | 96     | 96      |

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2021

### Exxon Mobil Corporation

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved