Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
1. IDENTIFICATION OF THE SUBS	STANCE/MIXTURE AND OF THE COM	PANY/UNDERTAKING
Product name	: Diala S4 ZX-I	
Product code	: 001E8701	
Manufacturer or supplier's de	etails	
Manufacturer/Supplier	: Shell India Markets Private Limited (U23201TN2004PTC053147) 2nd Floor, Campus 4A RMZ Millenia Park 143 Dr. MGR Road, Perungudi CHENNAI 600096 India	Ł
Telephone Telefax	: (+91) 04443450000 : (+91) 04443451516	
Emergency telephone number	: +91 22 6516 1058	

#### Recommended use of the chemical and restrictions on use

Recommended use	: Insulating oil.
-----------------	-------------------

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
		TVII/(COLO

Chemical nature : Fischer-Tropsch derived hydrocarbon base oil.

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Distillates (Fischer - Tropsch), heavy, C18- 50 – branched, cyclic and linear	848301-69-9	Xn; R65	Asp. Tox. 1; H304	95 - 100
Butylated hydroxytoluene	128-37-0	N; R50/53	Aquatic Chronic 1; H410 Aquatic Acute 1; H400	0.1 - 0.24

For explanation of abbreviations see section 16.

SAFETY DATA SHEET		
Diala S4 ZX-I		
Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
3. HAZARDS IDENTIFICATION		
Classification (REGULATION	I (EC) No 1272/2008)	
Aspiration hazard	: Category 1	
Label elements Hazard pictograms		
Signal word	: Danger	
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical haza HEALTH HAZARDS: H304 May be fatal if swallowed a ENVIRONMENTAL HAZARDS: Not classified as environmental h criteria.</li> </ul>	nd enters airways.
Precautionary statements	<ul> <li>Prevention: No precautionary phrases.</li> <li>Response: P331 Do NOT induce vomiting. P301 + P310 IF SWALLOWED: In CENTER/ doctor.</li> <li>Storage: P405 Store locked up.</li> <li>Disposal: P501 Dispose of contents/ contain disposal plant.</li> </ul>	

Hazardous components which must be listed on the label: Contains Distillates (Fischer - Tropsch), heavy, C18-50 - branched, cyclic and linear.

#### Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

4. FIRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	<ul> <li>Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.</li> <li>If persistent irritation occurs, obtain medical attention.</li> </ul>

# Diala S4 ZX-I

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
In case of eye contact	: Flush eye with copious quantities Remove contact lenses, if prese rinsing. If persistent irritation occurs, obta	nt and easy to do. Continue
If swallowed	: Call emergency number for your If swallowed, do not induce vom medical facility for additional trea spontaneously, keep head below If any of the following delayed sig within the next 6 hours, transpor facility: fever greater than 101° F breath, chest congestion or cont	iting: transport to nearest atment. If vomiting occurs v hips to prevent aspiration. gns and symptoms appear t to the nearest medical 5 (38.3°C), shortness of
Most important symptoms and effects, both acute and delayed	<ul> <li>If material enters lungs, signs an coughing, choking, wheezing, dit congestion, shortness of breath, The onset of respiratory symptor several hours after exposure.</li> <li>Defatting dermatitis signs and sy burning sensation and/or a dried Ingestion may result in nausea,</li> </ul>	fficulty in breathing, chest and/or fever. ms may be delayed for /mptoms may include a //cracked appearance.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings	equipment according to the
Notes to physician	: Potential for chemical pneumoni Call a doctor or poison control ce	

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media		er spray or fog. Dry chemical powder, carbon nd or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use	water in a jet.
Specific hazards during firefighting	A complex gases (smo Carbon mo occurs.	combustion products may include: mixture of airborne solid and liquid particulates and oke). noxide may be evolved if incomplete combustion d organic and inorganic compounds.
Specific extinguishing methods	•	uishing measures that are appropriate to local ces and the surrounding environment.
Special protective equipment for firefighters	gloves are	tective equipment including chemical resistant to be worn; chemical resistant suit is indicated if ct with spilled product is expected. Self-Contained

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
	Breathing Apparatus must be worn a confined space. Select fire fighte relevant Standards (e.g. Europe:	er's clothing approved to
6. ACCIDENTAL RELE		

Personal precautions, protective equipment and emergency procedures Environmental precautions	oid contact with skin and eyes. cal authorities should be advised if sig nnot be contained.	nificant spillages
Methods and materials for containment and cleaning up	ppery when spilt. Avoid accidents, cle event from spreading by making a bar other containment material. eclaim liquid directly or in an absorbent ak up residue with an absorbent such itable material and dispose of properly	rier with sand, earth t. as clay, sand or other
Additional advice	r guidance on selection of personal pr e Section 8 of this Safety Data Sheet. r guidance on disposal of spilled mate s Safety Data Sheet.	

#### 7. HANDLING AND STORAGE

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Product Transfer :	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.

# Diala S4 ZX-I

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
Packaging material	: Suitable material: For containers of steel or high density polyethylene. Unsuitable material: PVC.	
Container Advice	: Polyethylene containers should no temperatures because of possible	

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	IN OEL
Oil mist, mineral	Not Assigned	STEL (Mist)	10 mg/m3	IN OEL
Oil mist, mineral	Not Assigned	TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

#### Components with workplace control parameters

#### **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

ersion 2.7	Revision Date 10.05.2021	Print Date 11.05.202
Engineering measures	: The level of protection and types vary depending upon potential ex controls based on a risk assessm Appropriate measures include: Adequate ventilation to control air	posure conditions. Select ent of local circumstances.
	Where material is heated, sprayed greater potential for airborne cond	
	General Information: Define procedures for safe handli controls. Educate and train workers in the I measures relevant to normal activ product. Ensure appropriate selection, test equipment used to control exposu equipment, local exhaust ventilati Drain down system prior to equip maintenance. Retain drain downs in sealed stor subsequent recycle. Always observe good personal hy washing hands after handling the drinking, and/or smoking. Routine protective equipment to remove c contaminated clothing and footwe Practice good housekeeping.	hazards and control vities associated with this ting and maintenance of ure, e.g. personal protective on. ment break-in or age pending disposal or vgiene measures, such as material and before eating, ely wash work clothing and ontaminants. Discard
	Do not ingest. If swallowed, then a assistance	seek immediate medical

### Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	<ul> <li>No respiratory protection is ordinarily required under normal conditions of use.</li> <li>In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.</li> <li>If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.</li> <li>Check with respiratory protective equipment suppliers.</li> <li>Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.</li> <li>Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point &gt;65°C (149°F)].</li> </ul>
------------------------	---

### Diala S4 ZX-I

rsion 2.7	Revision Date 10.05.2021	Print Date 11.05.202	
Hand protection Remarks	<ul> <li>Where hand contact with the progloves approved to relevant stan US: F739) made from the followi suitable chemical protection. PV/gloves Suitability and durability of usage, e.g. frequency and durati resistance of glove material, dex from glove suppliers. Contamina replaced. Personal hygiene is a loare. Gloves must only be worn gloves, hands should be washed Application of a non-perfumed m For continuous contact we recombreakthrough time of more than a for &gt; 480 minutes where suitable short-term/splash protection we recognize that suitable gloves of may not be available and in this time maybe acceptable so long a and replacement regimes are fol a good predictor of glove resistant.</li> </ul>	<ul> <li>Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.</li> <li>For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for &gt; 480 minutes where suitable gloves can be identified. Fo short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is no a good predictor of glove resistance to a chemical as it is dependent on the taxet to input the more than 240 for material.</li> </ul>	
Eye protection	<ul><li>depending on the glove make an</li><li>If material is handled such that it</li></ul>	could be splashed into eyes	
	protective eyewear is recommen		
Skin and body protection	<ul> <li>Skin protection is not ordinarily re work clothes.</li> <li>It is good practice to wear chemi</li> </ul>		
Thermal hazards	: Not applicable		
Environmental exposure c	ontrols		
General advice	<ul> <li>Local guidelines on emission lim must be observed for the dischar vapour.</li> <li>Minimise release to the environm assessment must be made to en environmental legislation.</li> <li>Information on accidental release</li> </ul>	rge of exhaust air containing nent. An environmental sure compliance with local	

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: colourless
Odour Threshold	: Data not available

section 6.

# Diala S4 ZX-I

rsion 2.7	Revision Date 10.05.2021 Print Date 11.05.2021
рН	: Not applicable
pour point	: <= -40 °C / -40 °FMethod: ISO 3016
Melting / freezing point	Data not available
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)
Flash point	: 191 °C / 376 °F Method: ISO 2719
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.805 (20 °C / 68 °F)
Density	: 805 kg/m3 (20 °C / 68 °F) Method: ISO 3675
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n- octanol/water	: log Pow: > 6(based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: <= 12.00 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104
Explosive properties	: Not classified
Oxidizing properties	: Data not available

### Diala S4 ZX-I

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
Conductivity	: This material is not expected to be	a static accumulator.

#### **10. STABILITY AND REACTIVITY**

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

#### **11. TOXICOLOGICAL INFORMATION**

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
		Remarks: Aspiration into the lungs may cause chemical pneumonitis which can be fatal.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Skin corrosion/irritation		

### Product:

# Diala S4 ZX-I

Version 2.7 Revision Date 10.05.2021 Print Date 11.05.2021

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

#### Product:

Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Distillates (Fischer - Tropsch), heavy, C18-50 – branched, cyclic and linear	No carcinogenicity classification.
Butylated hydroxytoluene	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Butylated hydroxytoluene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

#### Reproductive toxicity

#### Product:

Version 2.7

Revision Date 10.05.2021

Print Date 11.05.2021

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

#### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### **STOT - repeated exposure**

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

#### **12. ECOLOGICAL INFORMATION**

Basis for assessment	<ul> <li>Ecotoxicological data have not been determined specifically for this product.</li> <li>Information given is based on a knowledge of the components and the ecotoxicology of similar products.</li> <li>Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).</li> </ul>
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met.

# Diala S4 ZX-I

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the clas	
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the clas	
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
<u>Components:</u> Butylated hydroxytoluene :		
M-Factor (Short-term (acute) aquatic hazard) M-Factor (Long-term (chronic) aquatic hazard)	: 1 : 1	
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegrada inherently biodegradable, but con persist in the environment.	
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based or products)	n information on similar
Mobility in soil		
Product:		
Mobility	<ul> <li>Remarks: Liquid under most env enters soil, it will adsorb to soil p mobile.</li> <li>Remarks: Floats on water.</li> </ul>	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	: Does not have ozone depletion pozone creation potential or globa	

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
	is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture., Causes physical fouling of aquatic organisms.	
13. DISPOSAL CONSIDERATIONS		
Disposal methods		
Waste from residues : Recover or recycle if possible. It is the responsibility of the waste g toxicity and physical properties of th determine the proper waste classific methods in compliance with applica Do not dispose into the environmen courses		the material generated to fication and disposal cable regulations.
	Waste product should not be allow ground water, or be disposed of in Waste, spills or used product is da Waste arising from a spillage or ta disposed of in accordance with pro preferably to a recognised collector competence of the collector or cor established beforehand. Do not dispose of tank water bottor drain into the ground. This will res contamination.	to the environment. angerous waste. Ink cleaning should be evailing regulations, or or contractor. The htractor should be
	MARPOL - see International Conv Pollution from Ships (MARPOL 73 technical aspects at controlling po	8/78) which provides
Contaminated packaging	: Dispose in accordance with preva to a recognized collector or contra the collector or contractor should b Disposal should be in accordance national, and local laws and regula	ctor. The competence of be established beforehand. with applicable regional,
Local legislation Remarks	: Disposal should be in accordance national, and local laws and regula	

### 14. TRANSPORT INFORMATION

### International Regulations

ADR Not regulated as a dangerous good

Version 2.7

Revision Date 10.05.2021

Print Date 11.05.2021

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### **15. REGULATORY INFORMATION**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

#### Other international regulations

#### The components of this product are reported in the following inventories:

EINECS	:	Not established.
TSCA	:	All components listed.

#### **16. OTHER INFORMATION**

#### Full text of R-Phrases

R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
R65	Harmful: may cause lung damage if swallowed.	
Full text of H-Statements		
	May be fotal if awallowed and enters airways	

H304	May be fatal if swallowed and enters airways.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard

Abbreviations and Acronyms : The quoted data are from, but not limited to, one or more

14/15

# Diala S4 ZX-I

Version 2.7	Revision Date 10.05.2021	Print Date 11.05.2021
	sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc). The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.	
SDS Regulation	: Regulation 1907/2006/EC	
Further information		
Training advice	: Provide adequate information, in operators.	struction and training for
Other information	: A vertical bar ( ) in the left margir from the previous version.	n indicates an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but no sources of information (e.g. toxic Health Services, material supplie IUCLID date base, EC 1272 regu	ological data from Shell ers' data, CONCAWE, EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.