Shell Chemicals



Technical Datasheet

ShellSol D70

Product Code Q7712

Region Europe

Product Category Aliphatic Mineral Spirits

CAS Registry Number 64742-47-8

EINECS Number 265-149-8

Description ShellSol D70 consists predominantly of C11- C14 paraffins and

naphthenes. Deep hydrogenation gives this solvent a very low aromatic

content, negligible amount of reactive impurities and a low, sweet

odour.

Typical Properties

Property	Unit	Method	Value
Water	% m/m	ASTM D1364	< 0.005
Density @15°C	kg/L	ASTM D4052	0.796
Coefficient of Cubic Expansion @20°C	10 ⁻⁴ /°C	Calculated	9
Refractive Index @20°C	-	ASTM D1218	1.439
Colour	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 10
Copper Corrosion (1hr @100°C)	-	ASTM D130	1
Doctor Test	-	ASTM D4952	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	1
Distillation, Initial Boiling Point	°C	ASTM D86	203
Distillation, Dry Point	°C	ASTM D86	237
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	0.01
Relative Evaporation Rate (Ether=1)	-	DIN 53170	800
Antoine Constant A #	kPa, °C	-	5.99080
Antoine Constant B #	kPa, °C	-	1753.00
Antoine Constant C #	kPa, °C	-	221.030

115 ShellSol D70 April 2016

Antoine Constants: Temperature range	°C	-	+80 to +215
Vapor Pressure @ 0°C	kPa	Calculated	0.01
Vapor Pressure @ 20°C	kPa	Calculated	0.05
Saturated Vapor Concentration @ 20°C	g/m³	Calculated	4
Paraffins	% m/m	GC	50
Naphthenes	% m/m	GC	50
Aromatics	mg/kg	SMS 2728	< 200
Benzene	mg/kg	GC	< 3
Sulfur	mg/kg	ISO 20846	< 0.5
Flash Point	°C	ASTM D93	78
Lower Explosion Limit in Air	% v/v		0.6
Upper Explosion Limit in Air	% v/v		5.5
Auto Ignition Temperature	°C	ASTM E659	236
Electrical Conductivity @ 20°C	pS/m	ASTM D4308	< 1
Dielectric Constant @ 20°C	-	-	2.1
Aniline Point	°C	ASTM D611	76
Kauri-Butanol Value	-	ASTM D1133	29
Pour Point	°C	ASTM D97	< -50
Viscosity @ 25°C	mm ² /s	ASTM D445	2.0
Surface Tension @ 20°C	mN/m	Du Nouy ring	26
Thermal Conductivity @ 20°C	W/m/°C		0.14
Hildebrand Solubility Parameter	(cal/cm ³) ^{1/2}	-	7.6
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization at T _{boil}	kJ/kg	-	250
Heat of Combustion (Net) @t 25°C	kJ/kg	-	45000
Specific Heat @ 20°C	kJ/kg/°C	-	2.0
Molecular Weight	g/mol	Calculated	174

^(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation: $\log P = A - B/(T+C)$

115 ShellSol D70 April 2016

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : www.astm.org International Organization for Standardization (ISO) : www.iso.org Deutsches Institut für Normung (DIN) : www.din.de

Shell Method Series (SMS) methods are issued by Shell Global Solutions International B.V., Shell Technology Centre, Amsterdam, The Netherlands. Requests for copies of SMS can be made through your local Shell Chemicals company.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

Quality

ShellSol D70 does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet on www.shell.com/chemicals.

Storage Handling

Provided proper storage and handling precautions are taken we would expect ShellSol D70 to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet on www.shell.com/chemicals.

Trademark

ShellSol is a Shell trademark.

All products purchased or supplied by Shell chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Shell chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Shell chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based or the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

The expression 'Shell Chemicals' refers to the companies of the Royal Dutch/Shell Group that are engaged in chemical businesses. Each of the companies that make up the Royal Dutch/Shell Group of companies is an independent entity and has its own separate identity.

115 ShellSol D70 April 2016